

MP | **INTRALOGISTIC**
MASTER IN PRODUCTIVITY



TRACTOR | ***TX1000 AC***

mar plast group



EL. PLATFORM TX 1000 AC

TECHNICAL FEATURES

FEATURES	00	MANUFACTURER		MP INTRALOGISTIC
	01	Model		TX 1000 AC
	02	Traction		Electric
	03	Type of driving		Rider
	04	Loading capacity	(t)	1.0
	05	Wheel axles (± 3 mm)	(mm)	550
WEIGHTS	06	Weight including battery	(Kgs)	430
WHEELS / STRUCTURE	07	Tyres (Superelastic, Pneumatic, Solid rubber)		SE (Superelastic)
	08	Front wheel dimensions		230 x 70
	09	Rear wheel dimensions		150 x 50
	10	Front wheel number (drive)		1
	11	Rear wheel number		2
	12	Rear wheel track	(mm)	550
DIMENSIONS	13	Operator dashboard height	(mm)	1408
	14	Operator seat height	(mm)	-
	15	Footrest height	(mm)	-
	16	Footrest height from ground	(mm)	185
	17	Max. Clearance	(mm)	60
	18	Platform length	(mm)	335
	19	Platform width	(mm)	630
	20	Total length	(mm)	1366
	21	Total width	(mm)	670
	22	Min. working aisle (recommended)	(mm)	900
	23	Min. aisle to turn at 180° (recommended)	(mm)	1500
	24	Turning radius	Wa (mm)	1200
*PERFORMANCES	25	Reduction gear ratio		1/16
	26	Max. speed without loading	Km/h	10 - adjustable
	27	Max. gradient without loading	%	10
	28	Service brake		Plugging
	29	Parking brake		Electro - mechanical
	30	Emergency brake		Electro - mechanical
	31	Driving detection sensor		350
	32	Nominal towing hook stress	F(N)	-
ELECTRIC FEATURES	33	Traction motor, capacity KB 60 min	(kW)	1.5 AC Type
	34	Battery		Lead acid
	35	Battery voltage	(V)	24 V
	36	Battery capacity	(Ah)	230
	37	Battery weight	(Kgs)	200
OTHERS	38	Kind of transmission		Driving wheel
	39	Average noise for the operator	dB (A)	< 70
	40	Steering gear		Electric steering
	41	Vibrations to the operator	m/s ²	< 2,5 m/s ²
		* The performances refer to the vehicle in perfect conditions, with charged battery and regular maintenance.		

MP INTRALOGISTIC
MASTER IN PRODUCTIVITY

